

A
Hinges & Pivots



Meets ANSI/BHMA A156.16

060 Flexible Door Stops 061

- Utilizes heavy gauge spring to maintain rigid protections
- Simple to install - only a screwdriver required
- Made from burnished wrought steel
- Packed disassembled for quick installation

Replaceable white rubber tip available

B
Pulls & Plates

Dimensions

Base Diameter: 1"

Tip Diameter: 19/16"

060 3" Projection

061 4" Projection

Finishes *steel*

Ives Finish	F3	F5	F10	F10B	F14	F15*	F26D	F-W**
BHMA	632	638	639	640	645	646	652	

* only available on 060

** only available on 061

C
Flush Bolts & Coordinators

D
Latches, Catches & Bolts



60 Base Door Stops 61

- Available in three sizes to accommodate varying areas of installation and door trim dimensions
- Made from solid brass or aluminum
- 61 also available in epoxy colored aluminum

Replaceable white/black rubber tip available

Dimensions

60 3-3/4" Projection, Base Diameter: 1"

61 3-1/8" Projection on brass units, 3-3/16" Projection on aluminum units, Base Diameter: 7/8", Tip Diameter: 5/8"

Finishes *brass*

Ives Finish	B3	B4	B5	B10	B10B	B15	B15A*	B26	B26D	B716**
BHMA	605	606	609	612	613	619	620	625	626	

Finishes *aluminum*

Ives Finish	A3	A5*	A10*	A10B	A14	A15*	A19*	A92	A716*	A-BLK	A-W*
BHMA	666		668	703	669	670	A19	673			

Finishes *zinc*

Ives Finish	Z605*	Z619*	Z716*
BHMA			

* only available on 61

** only available on 61 Schlage Carded or slim package of 15

Note: 61A - 716 ships with black rubber tips

E20
Stops

F
Exterior Hardware

G
Miscellaneous Hardware