

Hinges and pivots

Pin and barrel continuous hinges

711

Swing clear pin and barrel continuous hinge (steel and stainless steel)

- Edge guard
- May be difficult to install on inside walls
- 1/4" diameter pin with nylon self-lubricating, medical grade split bearing
- For doors weighing up to 300 pounds without reinforcing, 600 pounds with reinforcing
- 48" Maximum door width
- Non-handed, handing required for custom cut lengths
- Square edge door

Specifications

Standard length	83", 85", 95", 120"
Material substrate	▪ 711 - 14 Gauge type 304 stainless steel
Standard mounting hardware	▪ #10 X 1/2" Self drilling, self tapping screws ▪ #10 X 1" Wood screws
Certifications	▪ Meets ANSI/BHMA 156.26 ▪ UL10C listed (3 hour)

Options

HT	Hospital tip
----	--------------

Optional mounting hardware

SECHM	Security screws - hollow metal door and frame
SECWDHM	Security screws - 1/2 wood, 1/2 hollow metal
SECWDWD	Security screws - wood door and frame
WD	Wood door and frame

Finishes

BHMA	Description	Substrate	Finish
630	Satin Stainless Steel	Stainless steel	US32D



For single door applications:

For pairs of doors see chart and general information.

